

PRACHT®
PRO LINE

ROADRUNNER

THE PRACHT INSTANT PROGRAM



PRO LINE

HIGHEST QUALITY

SHORT DELIVERY TIME

PRACHT®

THE PRACHT INSTANT PROGRAM



APOLLO G2

- Swivelling, easy to install reflectors
- 1 and 2 beam design
- Thermically separated reflectors and ballast unit



TUBIS

- Especially tight - IP66/68/x9K approved
- Easy to clean, especially for the food industry
- 360° rotatable



COMO PRO

- Temperature resistant from -40°C up to +55°C
- Low glare, powerful lighting
- Suitable for high hall ceilings up to 25m



READY FOR DEL

PRO LINE - LUMINAIRES

APOLLO G2 Single lamp with 1 or 2 reflectors, cover PO (PRACHTOPAL®, impact resistant), 90° wide, R_a > 80, EEC A++, IP65.

P/N	Power	Luminous flux	Option	Length	Through-wiring	Weight
9380134w	1x33 W	4800 lm	ON/OFF	1260 mm	5 x 2,5 mm ²	2,7 kg
9380214w	1x56 W	8100 lm	ON/OFF	1260 mm	5 x 2,5 mm ²	2,7 kg
9380125w	1x33 W	4700 lm	ON/OFF	1560 mm	5 x 2,5 mm ²	3,1 kg
9380145w	1x49 W	7200 lm	ON/OFF	1560 mm	5 x 2,5 mm ²	3,1 kg
9300145w	1x49 W	7200 lm	ON/OFF	1560 mm	without	3,1 kg
9380195w	2x49 W	14400 lm	ON/OFF	1560 mm	5 x 2,5 mm ²	4,7 kg
9380175w	2x33 W	9400 lm	ON/OFF	1560 mm	5 x 2,5 mm ²	4,7 kg
9380140w	1x49 W	7200 lm	DIM-DALI	1560 mm	5 x 2,5 mm ² + 2 x 1,5 mm ²	3,1 kg
9380140wSF *	1x49 W	7200 lm	DIM-DALI	1560 mm	5 x 2,5 mm ² + 2 x 1,5 mm ²	3,1 kg
9380190w	2x49 W	14400 lm	DIM-DALI	1560 mm	5 x 2,5 mm ² + 2 x 1,5 mm ²	4,7 kg
9380280w	2x81 W	25000 lm	DIM-DALI	1560 mm	5 x 2,5 mm ² + 2 x 1,5 mm ²	4,7 kg

* SF = silicone-free

TUBIS Single lamp, cover PO (PRACHTOPAL®, impact resistant), 125° wide, R_a > 80, EEC A++, IP66/67/x9K.

P/N	Power	Luminous flux	Option	Length	Through-wiring	Weight
7203634	1x41 W	5400 lm	ON/OFF	1260 mm	without	4,0 kg
7203615	1x41 W	5600 lm	ON/OFF	1540 mm	without	4,0 kg
7203635	1x50 W	6700 lm	ON/OFF	1540 mm	without	4,0 kg
7283615	1x41 W	5600 lm	ON/OFF	1565 mm	5 x 2,5 mm ²	4,0 kg
7283635	1x50 W	6700 lm	ON/OFF	1565 mm	5 x 2,5 mm ²	4,0 kg
7a831455 *	1x83 W	10500 lm	ON/OFF	1565 mm	5 x 2,5 mm ²	4,0 kg
7283630	1x50 W	6700 lm	DIM-DALI	1540 mm	3 x 2,5 mm ² + 2 x 1,5 mm ²	4,0 kg

* TUBIS INDUSTRY with industry components

COMO PRO High bay luminaire, 100° wide, R_a > 80, 4000K, EEC A++, IP65

P/N	Power	Luminous flux	Option	Diameter	Through-wiring	Weight
96062121	1x150 W	20500 lm	DIM-DALI	380 mm	without	3,9 kg
96061121	1x200 W	27000 lm	DIM-DALI	380 mm	without	4,0 kg

Of course we will provide you with information about the availability of your requested luminaire at our wholesale partners. For further questions, please do not hesitate to contact us.

LIVERY IN 48H

**„THERE WILL NEVER BE ANY COMPROMISE
IN THE QUALITY OF MY PRACHT LUMINAIRES.“**

Alfred Pracht, founder, 1963